



## 800x800 Outdoor cabinet

### Design criteria

- . Filters can be removed and cleaned or replaced.
- . 1 or 1+1 aircon units can be installed in both doors.
- . Access to front and to side of cabinet.
- . Cabinet stand is designed for ULCT box mounting.
- . Front and side door are equipped with a 3 point locking mechanism and stoppers.
- . All doors can be either left or right handed, depending on site conditions.
- . Doors can open 90 degrees for rack mount units, and can also be removed for accessibility.
- . U- mount rack system, can be set up for access from either doors, and have 3x12 U adjustable depth rails to accommodate client requirement.

### Specifications

- . 800x800 foot print x 1840 height.
- . A total of 36U mounting space.
- . Consists of 3x 12U rails in front and back, each mounted separately to horizontal rails for easy adjustment.
- . Air-conditioning unit can accommodate up to a 1250W unit for maximum cooling.
- . 2x $\phi$ 32 holes in bottom corners for power run entry, and 20x  $\phi$ 20 holes for data / feeder entry.
- . Entire external frame are made of 3CR12 S/S epoxy coated.
- . Bottom support frame hot dip galvanized.
- . Fan unit with air filter system to create positive pressure to minimize dust in cabinet.



**Graffo** Innovative wireless infrastructure solutions

Tel: +27 (0)21 905-0010

Fax: +27 (0)21 905-0020

Web: [www.graffo.co.za](http://www.graffo.co.za)

800x800 outdoor cabinet  
with possible air conditioning units  
(door mount)  
Overall dimensions